



Registered Office

The Haugh, Blairgowrie,
Perthshire, PH10 7ER
Tel: (01250) 872261
Fax: (01250) 872727
E:Mail
insulation@proctorgroup.com
www.proctorgroup.com

Warranty from A Proctor Group (“APG”) to Aerodynamic Developments (“AD”) for distribution of Frameshield 100 and Wrapshield (“the Product”) by AD to Austral Bricks (“AB”)

APG warrants that for a period of 15 years from the date of sale the Product will perform its function as a vertically applied wall breather membrane as part of a proprietary cladding system. The Product must be installed in accordance with AB’s installation instructions [for this warranty to apply]. This warranty is only valid if the Product is not left exposed for more than 2 months.

In the event of a Product failing to perform the said function APG shall either, at APG’s sole option, replace the defective product or refund the price of defective product. Furthermore, APG warrants the Product will be free from manufacturing defects and will comply with the specification as detailed in appendix A as attached.

This is the sole remedy granted by APG for breach of this warranty.

In no event shall APG be liable for any indirect or direct consequential losses or damage howsoever caused.

This is the sole extent of the warranty given by APG in relation to the supply of the Product to AD for onward distribution to AB and is given solely in relation to that arrangement. This warranty is given in lieu of all other warranties, express or implied, which are hereby expressly excluded to the fullest extent permitted by law.



Appendix A

Material Base	Polypropylene	
Colour	Various	
Weight	g/m ² 175	Edana 40:3:90
MD Tensile Strength N	320	Edana 20:2:89
CD Tensile Strength N	190	Edana 20:2:89
MD Nail Tear Strength N	155	MOAT 27:5.4.1
CD Nail Tear Strength N	135	MOAT 27:5.4.1
Mason Jar Pass/Fail	Pass	BS 4016
M.V.T.R. g/m ² /24 hrs	2287	BS 3177
M.V.T.R. g/m ² /24 hrs	1590	DIN 53122
Flame Retardancy Pass/Fail	Pass	DIN 4102 Part 1 B2
Flame Retardancy	Class E	EN 11925-2
UV Stability Months	4	STM 044